

type number	nominal thread diameter	bolt length	🔥
NSM 6X10_ZNCR	M6	10	🔥 🔵
NSM 6X10_GMT	M6	10	🔥 🔵
NSM 6X20_ZNCR	M6	20	🔥 🔵
NSM 6X20_GMT	M6	20	🔥 🔵



product description: The bolt with nut NSM 6X10 is used to connect cable trays or cable trays with accessories, or to attach trays to supporting structures. Used for the same purpose on cable ladder systems.

The bolt and the nut provide a conductive equipotential bond up to 25 A.

The bolt with nut NSM 6X20 is used to fasten partition KLP or distance bracket KLDI 35X110 to the cable ladder. The set can also be used to connect routes or to attach routes to supports - wherever the length of the bolt NSM 6X10 is not sufficient.

To protect the cables, the bolt head is inside the cable tray.

Bolt tightening moment - 9.7 Nm.

Key size - 10

A bolt with a GMT surface finish is used for a tray with an F surface finish.

surface finish: ZNCR - electrolytic galvanised
 GMT - GEOMET, non electrolytic plating, aluminum-zinc-layer 5-15 µm

sales amount: á 100 pcs

klasifikace 📌: ČSN 73 0895 P 90-R
 DIN 4102-12 E 90
 STN 92 0205 PS 90

Fire classification depends on the specific conditions of the cable tray, detailed in the catalog Systems with maintained functionality in fire

- 🔥 products are approved for standard constructions
- 🔵 products are approved for non-standard constructions

storage: ČSN EN 60721-3-1

